

# Diebold's advanced-function, through-the-wall walk-up ATM is the optimum way to help achieve your business goals

## Increased Functionality

Modular construction allows you to add features and functionalities quickly and cost effectively.

## Enhanced Design

Contemporary, sleek design fits any interior or exterior surroundings.

## Open System Software Support

Opteva™ terminals are powered by Agilis™, Diebold's high-performance software, which interfaces with a variety of multiple-vendor products to decrease your need for backend support.

## Reliability

With large-capacity consumables and intelligent modules that forecast predictive maintenance needs, you can count on maximum availability for each machine.

## Installation Flexibility

Can easily be retrofitted to fit existing full-function through-the-wall automated teller machine (ATM) openings.

## Enhanced Security Features

Reduce risk exposure with enhanced ATM modules incorporating the latest in fraud-preventive mechanisms.

## Simplified Service

Lower ongoing operating costs with our intuitive graphical interface that simplifies maintenance functions and makes it easy to train new branch personnel.



# Opteva 760 Features

Build your self-service delivery channel upon the power of Opteva hardware, Agilis software and Diebold Premier Services™. Together, they provide everything you need today, yet enable you to add new features and functions with unparalleled ease anytime tomorrow. Turn to Diebold for the complete self-service solution: hardware, software, and total services and support. Make it simple. Make it Diebold, the one company that can maximize the return on your self-service investment.

### Architecture:

Ergonomically designed fascia meets accessibility standards

Minimized ATM footprint offers the most functionality for the footprint size

### Display Options:

15.1-inch consumer LCD display delivers attention-getting graphics to increase advertising and cross-selling impact

Indoor and outdoor touch-screen options with or without function keys

Sunlight viewable and privacy filter options

### Enhanced Operator Interface:

10.4-inch color LCD rear monitor with available touch-screen capability provides analysis of the ATM as well as a variety of diagnostics and other service benefits

Adjustable alphanumeric keyboard and integrated pointing device

### Enhanced Security:

Every module was designed with security in mind

Fraud-resistant dispenser and card reader, consumer awareness mirrors, encrypting PIN pad, duress alarm, universal camera mounts, available ink dye system and much more

### Deposit Automation Options:

Envelope depositor with integrated dispenser provides one entry point for both presenting and receiving envelopes

Intelligent Depository Module™ accepts envelope-free checks for direct deposit verification and credit

Bulk note acceptor allows up to 100-note bundles to be deposited for automatic authentication and credit to the consumer's account

### Advanced Function Dispenser (AFD) Options:

Two to five multimedia cassettes for increased throughput and efficiencies

AFD utilizing proven friction pick technology

Divert cassette with separate retract and divert compartments

### Printer Options:

The industry's first two-color graphical thermal 80 mm receipt printer and A4 or 8.5-inch wide statement printer enable high-resolution graphics for easy reading and marketing opportunities

**DIEBOLD OPTEVA 760**  
Advanced-function, Through-the-wall Walk-up ATM

## Opteva 760 Specifications

Powerful Intel® Pentium® 4 processor

Consumer awareness mirrors

Large-capacity read/write CD-ROM drive

Microsoft® Windows® XP operating system

Consumer display

Printer options

- Two-color graphical thermal receipt and statement printers
- Graphical thermal journal printer

Headphone jack

Encrypting PIN pad

AFD with friction pick technology

Security chest

- UL 291 Level I
- CEN I
- CEN III
- CEN IV



Custom color options available

Universal camera mount

Dimensions

**Height:**

62.75 inches (1,594 mm)

**Width:**

31.25 inches (794 mm)

**Depth:**

40.875 inches (1,038 mm)

**Weight with five-high UL 291 Level 1 safe:**

1,535 lbs (696 kg)

**Weight with five-high CEN IV safe:**

2,235 lbs (1,014 kg)

Multi-colored, programmable lead-through indicators

Card reader options

- Manual insert (dip)
- Motorized options
- Smart card options

Deposit automation options

- Envelope depositor
- Intelligent Depository Module
- Bulk note acceptor

Optional barcode reader

Coin dispenser

**Total Solutions:**  
Opteva Hardware  
Agilis Software  
Diebold Premier Services  
Installation  
Supplies  
Financing

**Diebold, Incorporated**  
Post Office Box 3077  
Dept. 9-B-16  
North Canton, Ohio 44720-8077

800.999.3600 USA  
330.490.4000 International  
e-mail: [productinfo@diebold.com](mailto:productinfo@diebold.com)  
[www.diebold.com](http://www.diebold.com)



*We won't rest.*

Diebold is a registered trademark of Diebold, Incorporated. Intelligent Depository Module, Opteva, Agilis and Diebold Premier Services are trademarks of Diebold, Incorporated. ©Diebold, Incorporated 2003. All rights reserved. Microsoft and Windows are trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. Intel and Pentium are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries. Litho in U.S.A. 10m 0103.9 File No. 79-804

Printed on recycled paper